



# Ultra Guard Neopor Roof Insulation



Ultra Guard Neopor is insulation board that comes with a 2 sided, high barrier facer that protects against many types of chemicals. This closed cell EPS board is ideal in re-cover applications or new construction. It is well-suited for single-ply roof applications that employ mechanically fastened or ballasted TPO, PVC, EPDM and CSPE membranes. Ultra Fold is a tough product that holds its R-value and is resistant to bacteria, fungus, rot, mold and mildew.



Ultra Fold offers a stable R-value, dimensional stability, excellent water resistance and compressive strength properties. Facers can be clear or reflective.

Wk



- **Great recovery board applications**
- **No off-gassing**
- **1/2" - 4" thickness (4'x8')**
- **Light-weight, high strength**
- **Compatible with other insulations**

**Higher R-Value**



## Ultra Guard Neopor EPS Properties

Thickness	R-Value @ 23° F	R-Value @ 75° F	PSI CR @ 10%
3"	15.03	13.44	13.0
2"	10.02	8.96	13.0
1.5"	7.52	6.72	13.0
1"	5.01	4.48	13.0
.75"	3.78	3.36	13.0
.5"	2.51	2.24	13.0

### Contact

**John Calkins 920-889-0021 jcedisonassc@yahoo.com**

**Plymouth Foam**  
**1800 Sunset Dr.**  
**Plymouth, WI 53073**  
**920-889-0021**  
**800-669-1176**  
**plymouthfoam.com**